

IN THE CLAIMS

This listing of the claim will replace all prior versions and listings of claim in the present application.

Listing of Claims

1. (currently amended) A storage device system comprising:
a plurality of storage devices in which information is stored;
a storage device control section for controlling storage of information in said plurality of storage devices;
a connection unit connected to said storage device control section;
a first processor that is connected to a local area network (LAN) external to said storage device system, that converts data of a file access form received over said LAN into data of a block access form; and
a second processor that is connected to said storage device control section via said connection unit, that accesses said plurality of storage devices via said connection unit and said storage device control section in response to data of the block access form issued from said first processor, and that controls activation of said first processor including resetting said first processor by said second processor, re-supplying power to said first processor and activating a Basic Input/Output System (BIOS) of said first processor.

2. (previously presented) A storage device system according to Claim 19, further comprising:
a second communication control section connected on a second network external to said storage device system,

wherein said first communication control section is formed with the same circuit board as said second communication control section is.

3. (previously presented) A storage device system according to Claim 1, wherein said first processor diagnoses the hardware thereof, wherein said second processor issues a request for start of hardware diagnosis of said first processor to said first processor.

4. (previously presented) A storage device system according to Claim 3, further comprising:

a management terminal connected to each of said first and second processors,

wherein said second processor issues a request for start of first processing to said first processor, and

wherein said first processor acquires first software from said management terminal in response to the first processing start request issued from said second processor.

5. (original) A storage device system according to Claim 4, wherein said first processor acquires second software from said management terminal under the control of the first software acquired from said management terminal, and writes the second software in said plurality of storage devices via said connection unit and said storage device control section.

6. (previously presented) A storage device system according to Claim 5, wherein said second processor issues a request for start of second processing to said first processor,

wherein said first processor acquires the second software written in said plurality of storage devices via said connection unit and said storage device control section in response to the second processing start request issued from said second processor.

7. (original) A storage device system according to Claim 4, wherein both the first processing start request and second processing start request contain time instant information.

8. (previously presented) A storage device system according to Claim 19, wherein said first communication control section includes a storage device in which third software is stored,

wherein said first processor activates the third software so as to activate said first communication control section, and waits for a request issued from said second processor.

9. (currently amended) A storage device system according to Claim 8, further comprising:

a second communication control section that is connected on a second network external to said storage device system,

wherein said first communication control section is formed with the same circuit board as said second communication control section is.

10. (previously presented) A storage device system according to Claim 9, wherein said first processor diagnoses the hardware thereof, and wherein said second processor issues a request for start of hardware diagnosis of said first processor to said first processor.

11. (previously presented) A storage device system according to Claim 10, further comprising:
a management terminal connected to each of said first communication control section and said second communication control section,
wherein said second processor issues a request for start of first processing to said first processor, and
wherein said first processor acquires first software from said management terminal in response to the first processing start request issued from said second processor.

12. (original) A storage device system according to Claim 11, wherein said first processor acquires second software from said management terminal under the control of the first software acquired from said management terminal, and writes the second software in said plurality of storage devices via said connection unit and said storage device control section.

13. (previously presented) A storage device system according to Claim 12, wherein said second processor issues a request for start of second processing to said first processor, and

wherein said first processor acquires the second software written in said plurality of storage devices via said connection unit and said storage device control section in response to the second processing start request issued from said second processor.

14. (original) A storage device system according to Claim 11, wherein both said first processing start request and said second processing start request contain time instant information.

15. (currently amended) A method of activating a storage device system that comprises a plurality of storage devices in which information is stored, a storage device control section which controls storage of information in said plurality of storage devices, a connection unit connected to said storage device control section, a first processor that is connected to a local area network (LAN) external to said storage device system and that converts data of a file access form received over said LAN into data of a block access form, and a second processor that is connected to said storage device control section via said connection unit, and that accesses said plurality of storage devices via said connection unit and said storage device control section in response to the data of the block access form issued from said first processor, said method comprising the steps of:

controlling, by said second processor, activation of said first processor
including resetting said first processor by said second processor, re-supplying
power to said first processor and activating a Basic Input/Output System
(BIOS) of said first processor;

issuing, by said second processor, a request for start of hardware
diagnosis of said first processor to said first processor; and

performing, by said first processor, hardware diagnosis in response to
the hardware diagnosis start request issued from said second processor.

16. (previously presented) A method according to Claim 15,
said method further comprising the steps of:

issuing, by said second processor, a request for start of first processing
to said first processor; and

acquiring, by said first processor, first software from a management
terminal in response to the first processing start request issued from said
second processor.

17. (previously presented) A method according to Claim 16,
further comprising the steps of:

acquiring, by said first processor, second software from said
management terminal under control of the first software acquired from said
management terminal, and writing the second software in said plurality of
storage devices via said connection unit and said storage device control
section.

18. (previously presented) A method according to Claim 17, further comprising the steps of:

issuing, by said second processor, a request for start of second processing to said first processor; and

acquiring, by said first processor, the second software written in said plurality of storage devices via said connection unit and said storage device control section in response to the second processing start request issued from said second processor.

19. (previously presented) A storage device according to claim 1, wherein said first and said second processors form part of a first communication control section.